

Long entry thread metric



AGRO combination conduit glands Progress® EMC nickel-plated brass with integrated cable gland

Type approval: Progress MS Kombi EMC

- One-piece sealing insert
- not overall length insulated

| | |
|------------------------------------|--|
| Article no: | 1710.80.17.080.2 |
| E-No: | 126638469 |
| EAN: | 7611614145631 |
| Material | Nickel-plated brass |
| Seal | TPE |
| O-ring | NBR |
| Operation temperature | -40°C / +100°C |
| Strain relief | Version A acc. to EN 62444 |
| Protection class | Cable gland IP 68 |
| Note | The max. clamping range depends on the conduit inner diameter |
| Properties | Excellent shield contact through the contact sleeve with the braided shield terminating in the screwed cable gland |
| Entry thread (G) | M16x1.5 |
| Outer diameter | 5/16" mm |
| Clamping range without insert min. | 6.0 mm |
| Clamping range without insert max. | 8.0 mm |
| Wrench size | 18/21 mm |
| Dimension (H) | 38 mm |
| Thread length (L) | 10 mm |
| Dispatch | 25 |

Depending on the type of conduit, the stabilising bush must be ordered separately. Available with sealing inserts conformity with EN 45545 / NFPA 130. When placing an inquiry, prefix the article number by the capital F.