


## Cable glands Progress® AgreenO nickel-plated brass lead-free



### Short entry thread metric

- Two-piece sealing insert
- not overall length insulated

|                                    |                              |
|------------------------------------|------------------------------|
| <b>Article no:</b>                 | <b>1000.40LF</b>             |
| E-No:                              | 121086258                    |
| EAN:                               | 7611614346618                |
| Material                           | Brass CuZn21Si3P lead-free   |
| Surface                            | Nickel-plated                |
| Identification                     | 1 groove                     |
| Seal                               | TPE                          |
| O-ring                             | NBR                          |
| Operation temperature              | -40°C / +100°C               |
| Strain relief                      | Version A acc. to EN 62444   |
| Protection class                   | IP 68 (up to 10 bar) / IP 69 |
| Entry thread (G)                   | M40x1.5                      |
| Clamping range with insert min.    | 24.0 mm                      |
| Clamping range with insert max.    | 28.5 mm                      |
| Clamping range without insert min. | 28.5 mm                      |
| Clamping range without insert max. | 33.0 mm                      |
| Wrench size                        | 46 mm                        |
| Dimension (H)                      | 31 mm                        |
| Thread length (L)                  | 8 mm                         |
| UL - clamping range                | 27.0-27.0 mm                 |
| Dispatch                           | 10                           |

### Available on request:

- Entry thread Pg and NPT