

## Cable glands Progress® AgreenO EMC nickel-plated brass lead-free with con

**Short entry thread metric**

- One-piece sealing insert
- not overall length insulated

|                       |                                                                                                                    |
|-----------------------|--------------------------------------------------------------------------------------------------------------------|
| <b>Article no:</b>    | <b>1080.17.100LF</b>                                                                                               |
| E-No:                 | 121188238                                                                                                          |
| EAN:                  | 7611614347608                                                                                                      |
| Material              | Brass CuZn21Si3P lead-free                                                                                         |
| Surface               | Nickel-plated                                                                                                      |
| Identification        | 1 groove                                                                                                           |
| Contact sleeve        | Brass CuZn21Si3P lead-free                                                                                         |
| Seal                  | TPE                                                                                                                |
| O-ring                | NBR                                                                                                                |
| Operation temperature | -40°C / +100°C                                                                                                     |
| Strain relief         | Version A acc. to EN 62444                                                                                         |
| Protection class      | IP 68 (up to 10 bar) / IP 69                                                                                       |
| Properties            | Excellent shield contact through the contact sleeve with the braided shield terminating in the screwed cable gland |
| Entry thread (G)      | M16x1.5                                                                                                            |
| Clamping range min.   | 8.0 mm                                                                                                             |
| Clamping range max.   | 10.0 mm                                                                                                            |
| Wrench size           | 18 mm                                                                                                              |
| Dimension (H)         | 25 mm                                                                                                              |
| Thread length (L)     | 5 mm                                                                                                               |
| Dispatch              | 50                                                                                                                 |

**Available on request:**

- Entry thread Pg and NPT