


Cable glands Progress® EMC powerCONNECT nickel-plated brass



Short entry thread metric

Type approval: Progress EMV powerCONNECT

- Two-piece sealing insert
- not overall length insulated

Article no:	1084.20
E-No:	121062428
EAN:	7611614312569
Material	Nickel-plated brass
Seal	TPE
O-ring	NBR
Operation temperature	-60°C / +100°C
Strain relief	Version A acc. to EN 62444
Protection class	IP 68 (up to 10 bar) / IP 69
NEMA Type rating	4X
Properties	For high leakage currents, concentric 360° shield contact ensure extremely low transfer resistance and transfer impedance. Compact design
Entry thread (G)	M20x1.5
Clamping range with insert min.	8.0 mm
Clamping range with insert max.	11.0 mm
Clamping range without insert min.	11.0 mm
Clamping range without insert max.	15.0 mm
Cable shield diameter	13.4
Inner diameter	11.9 mm
Wrench size	24 mm
Dimension (H)	32 mm
Thread length (L)	6 mm
Additional note	-
Dispatch	25

1 = One-piece sealing insert

Available with sealing inserts conformity with EN 45545 / NFPA 130. When placing an inquiry, prefix the article number by the capital F.

Available on request:

- Stainless steel A2 or A4
- Entry thread Pg and NPT