


## Cable glands Progress® EMC powerCONNECT nickel-plated brass

**Short entry thread metric****Type approval: Progress EMV powerCONNECT**

- Two-piece sealing insert
- not overall length insulated

<b>Article no:</b>	<b>1084.50</b>
E-No:	121062828
EAN:	7611614312637
Material	Nickel-plated brass
Seal	TPE
O-ring	NBR
Operation temperature	-60°C / +100°C
Strain relief	Version A acc. to EN 62444
Protection class	IP 68 (up to 10 bar) / IP 69
NEMA Type rating	4X
Properties	For high leakage currents, concentric 360° shield contact ensure extremely low transfer resistance and transfer impedance. Compact design
Entry thread	M50x1.5
Clamping range with insert min.	33.0 mm
Clamping range with insert max.	37.0 mm
Clamping range without insert min.	37.0 mm
Clamping range without insert max.	42.0 mm
Cable shield diameter	38.7
Inner diameter	37.7 mm
Wrench size	55 mm
Dimension H	44.5 mm
Thread length L	9 mm
Additional note	-
Dispatch	10

1 = One-piece sealing insert

Available with sealing inserts conformity with EN 45545 / NFPA 130. When placing an inquiry, prefix the article number by the capital F.

**Available on request:**

- Stainless steel A2 or A4
- Entry thread Pg and NPT