

## Cable glands Progress® nickel-plated brass



### Long entry thread metric

#### Type approval: Progress MS

- One-piece sealing insert
- not overall length insulated

|                       |                              |
|-----------------------|------------------------------|
| Article no:           | 1100.20.110                  |
| E-No:                 | 121099518                    |
| EAN:                  | 7611614104799                |
| Material              | Nickel-plated brass          |
| Seal                  | TPE                          |
| O-ring                | NBR                          |
| Operation temperature | -40°C / +100°C               |
| Strain relief         | Version A acc. to EN 62444   |
| Protection class      | IP 68 (up to 10 bar) / IP 69 |
| NEMA Type rating      | 4X                           |
| Entry thread (G)      | M20x1.5                      |
| Clamping range min.   | 8.0 mm                       |
| Clamping range max.   | 11.0 mm                      |
| Wrench size           | 24 mm                        |
| Dimension (H)         | 21 mm                        |
| Thread length (L)     | 10 mm                        |
| UL - clamping range   | 9.0-11.0 mm                  |
| Dispatch              | 50                           |

1 = Metric coarse-pitch thread (with VDE test report)

Available with sealing inserts conformity with EN 45545 / NFPA 130. When placing an inquiry, prefix the article number by the capital F.