

## Cable glands Progress® stainless steel A2



### Long entry thread metric

#### Type approval: Progress S2

- Two-piece sealing insert
- not overall length insulated

|                                    |                                                    |
|------------------------------------|----------------------------------------------------|
| Article no:                        | <b>1100.32.94</b>                                  |
| E-No:                              | 121624708                                          |
| EAN:                               | 7611614133904                                      |
| Material                           | CrNi stainless steel A2 (DIN EN 1.4305 / AISI 303) |
| Identification                     | 1 groove                                           |
| Seal                               | TPE                                                |
| O-ring                             | NBR                                                |
| Operation temperature              | -40°C / +100°C                                     |
| Strain relief                      | Version A acc. to EN 62444                         |
| Protection class                   | IP 68 (up to 10 bar) / IP 69                       |
| Entry thread                       | M32x1.5                                            |
| Clamping range with insert min.    | 17.0 mm                                            |
| Clamping range with insert max.    | 21.0 mm                                            |
| Clamping range without insert min. | 21.0 mm                                            |
| Clamping range without insert max. | 25.5 mm                                            |
| Wrench size                        | 36 mm                                              |
| Dimension H                        | 28 mm                                              |
| Thread length L                    | 13 mm                                              |
| Dispatch                           | 25                                                 |

Available with sealing inserts conformity with EN 45545 / NFPA 130. When placing an inquiry, prefix the article number by the capital F.