

## Cable glands Progress® stainless steel A2 for high temperature applications



### Long entry thread metric

#### Type approval: Progress S2 HT

- Two-piece sealing insert
- not overall length insulated

|                                    |                                                    |
|------------------------------------|----------------------------------------------------|
| Article no:                        | 1100.40.96                                         |
| E-No:                              | 121614808                                          |
| EAN:                               | 7611614133843                                      |
| Material                           | CrNi stainless steel A2 (DIN EN 1.4305 / AISI 303) |
| Identification                     | 1 groove                                           |
| Seal                               | FPM                                                |
| O-ring                             | FPM                                                |
| Operation temperature              | -40°C / +200°C                                     |
| Strain relief                      | Version A acc. to EN 62444                         |
| Protection class                   | IP 68 (up to 10 bar) / IP 69                       |
| Entry thread (G)                   | M40x1.5                                            |
| Clamping range with insert min.    | 24.0 mm                                            |
| Clamping range with insert max.    | 28.5 mm                                            |
| Clamping range without insert min. | 28.5 mm                                            |
| Clamping range without insert max. | 33.0 mm                                            |
| Wrench size                        | 46 mm                                              |
| Dimension (H)                      | 31 mm                                              |
| Thread length (L)                  | 13 mm                                              |
| Dispatch                           | 10                                                 |