

## Cable glands Progress® stainless and acid-resistant steel A4 for high temper

**Long entry thread metric****Type approval: Progress S4 HT**

- One-piece sealing insert
- not overall length insulated

|                       |                                                                                   |
|-----------------------|-----------------------------------------------------------------------------------|
| <b>Article no:</b>    | <b>1100.40.98.330</b>                                                             |
| E-No:                 | 121603808                                                                         |
| EAN:                  | 7611614132792                                                                     |
| Material              | Stainless steel and acid resistant steel A4<br>CrNiMo (DIN EN 1.4435 / AISI 316L) |
| Identification        | 2 grooves                                                                         |
| Seal                  | FPM                                                                               |
| O-ring                | FPM                                                                               |
| Operation temperature | -40°C / +200°C                                                                    |
| Strain relief         | Version A acc. to EN 62444                                                        |
| Protection class      | IP 68 (up to 10 bar) / IP 69                                                      |
| Entry thread (G)      | M40x1.5                                                                           |
| Clamping range min.   | 28.5 mm                                                                           |
| Clamping range max.   | 33.0 mm                                                                           |
| Wrench size           | 46 mm                                                                             |
| Dimension (H)         | 31 mm                                                                             |
| Thread length (L)     | 13 mm                                                                             |
| Dispatch              | 10                                                                                |

1 = Metric coarse-pitch thread (with VDE test report)