


## Long entry thread metric

**AGRO Adapter Progress® nickel-plated brass with integrated cable gland****Type approval: Progress MS Adapter**

- One-piece sealing insert
- overall length insulated

|                       |                                                               |
|-----------------------|---------------------------------------------------------------|
| <b>Article no:</b>    | <b>1165.12</b>                                                |
| E-No:                 | 126658310                                                     |
| EAN:                  | 7611614141862                                                 |
| Material              | Nickel-plated brass                                           |
| Seal                  | TPE                                                           |
| O-ring                | NBR                                                           |
| Operation temperature | -40°C / +100°C                                                |
| Strain relief         | Version A acc. to EN 62444                                    |
| Protection class      | Cable gland IP 68                                             |
| Note                  | The max. clamping range depends on the conduit inner diameter |
| Thread outside        | M12x1.5                                                       |
| Internal thread       | M12x1.5                                                       |
| Clamping range min.   | 5.0 mm                                                        |
| Clamping range max.   | 6.5 mm                                                        |
| Wrench size           | 15 mm                                                         |
| Dimension (H)         | 32 mm                                                         |
| Thread length (L)     | 10 mm                                                         |
| Additional note       | -                                                             |
| Dispatch              | 50                                                            |

1 = Metric coarse-pitch thread (with VDE test report)

Available with sealing inserts conformity with EN 45545 / NFPA 130. When placing an inquiry, prefix the article number by the capital F.