


## Long entry thread metric

**AGRO Adapters Progress® nickel-plated brass with integrated EMC cable gland****Type approval: Progress MS Kombi EMC**

- One-piece sealing insert
- not overall length insulated

|                                    |                                                                                                                    |
|------------------------------------|--------------------------------------------------------------------------------------------------------------------|
| <b>Article no:</b>                 | <b>1165.80.12.060</b>                                                                                              |
| E-No:                              | 126648310                                                                                                          |
| EAN:                               | 7611614141961                                                                                                      |
| Material                           | Nickel-plated brass                                                                                                |
| Contact sleeve                     | Nickel-plated brass                                                                                                |
| Seal                               | TPE                                                                                                                |
| O-ring                             | NBR                                                                                                                |
| Operation temperature              | -40°C / +100°C                                                                                                     |
| Strain relief                      | Version A acc. to EN 62444                                                                                         |
| Protection class                   | Cable gland IP 68                                                                                                  |
| Note                               | -                                                                                                                  |
| Properties                         | Excellent shield contact through the contact sleeve with the braided shield terminating in the screwed cable gland |
| Thread outside                     | M12x1.5                                                                                                            |
| Internal thread                    | M12x1.5                                                                                                            |
| Clamping range without insert min. | 4.5 mm                                                                                                             |
| Clamping range without insert max. | 6.0 mm                                                                                                             |
| Wrench size                        | 15 mm                                                                                                              |
| Dimension H                        | 34 mm                                                                                                              |
| Thread length L                    | 10 mm                                                                                                              |
| Dispatch                           | 50                                                                                                                 |

1 = Metric coarse-pitch thread (with VDE test report)

Available with sealing inserts conformity with EN 45545 / NFPA 130. When placing an inquiry, prefix the article number by the capital F.