


## Cable glands Progress® EMC nickel-plated brass with contact sleeve



### Long entry thread Pg

#### Type approval: Progress MS EMV

- One-piece sealing insert
- not overall length insulated

|                       |                                                                                                                    |
|-----------------------|--------------------------------------------------------------------------------------------------------------------|
| Article no:           | 1180.42.410                                                                                                        |
| E-No:                 | 121038818                                                                                                          |
| EAN:                  | 7611614119731                                                                                                      |
| Material              | Nickel-plated brass                                                                                                |
| Contact sleeve        | Nickel-plated brass                                                                                                |
| Seal                  | TPE                                                                                                                |
| O-ring                | NBR                                                                                                                |
| Operation temperature | -40°C / +100°C                                                                                                     |
| Protection class      | IP 68 (up to 10 bar) / IP 69                                                                                       |
| NEMA Type rating      | 4X                                                                                                                 |
| Properties            | Excellent shield contact through the contact sleeve with the braided shield terminating in the screwed cable gland |
| Entry thread (G)      | Pg 42                                                                                                              |
| Clamping range min.   | 37.0 mm                                                                                                            |
| Clamping range max.   | 41.0 mm                                                                                                            |
| Wrench size           | 55 mm                                                                                                              |
| Dimension (H)         | 36 mm                                                                                                              |
| Thread length (L)     | 15 mm                                                                                                              |
| Dispatch              | 10                                                                                                                 |

Available with sealing inserts conformity with EN 45545 / NFPA 130. When placing an inquiry, prefix the article number by the capital F.