


## Quickseal cable grommets



### Metric rating

· Dark grey RAL 7001

|                                    |                                                                                                                    |
|------------------------------------|--------------------------------------------------------------------------------------------------------------------|
| <b>Article no:</b>                 | <b>14.582.34</b>                                                                                                   |
| E-No:                              | 121810438                                                                                                          |
| EAN:                               | 7611614200620                                                                                                      |
| Material                           | EPDM                                                                                                               |
| Operation temperature              | -40°C / +110°C                                                                                                     |
| Protection class                   | IP 67                                                                                                              |
| Properties                         | Halogen-free, all-round IP 67 protection thanks to the "pushout-membrane", resistant to chemicals and weatherproof |
| Application                        | Suitable for holes in materials of 1 - 4 mm (M16 - M50), or M12 from 0.5 - 2 mm                                    |
| Diameter A                         | 16.5 mm                                                                                                            |
| Clamping range without insert min. | 5.0 mm                                                                                                             |
| Clamping range without insert max. | 9.0 mm                                                                                                             |
| Material thickness                 | 1-4 mm                                                                                                             |
| Dimension C                        | 11.0 mm                                                                                                            |
| Diameter D                         | 21.0 mm                                                                                                            |
| Dispatch                           | 50                                                                                                                 |