

## Cable glands Progress® AgreenO EMC nickel-plated brass lead-free with con



## Long entry thread metric

- One-piece sealing insert
- not overall length insulated

|                       |  |
|-----------------------|--|
| Article no:           | 1180.63.500LF  |
| E-No:                 | 121190138  |
| EAN:                  | 7611614347882  |
| Material              | Brass CuZn21Si3P lead-free   |
| Surface               | Nickel-plated  |
| Identification        | 1 groove   |
| Contact sleeve        | Brass CuZn21Si3P lead-free   |
| Seal                  | TPE  |
| O-ring                | NBR  |
| Operation temperature | -40°C / +100°C   |
| Strain relief         | Version A acc. to EN 62444   |
| Protection class      | IP 68 (up to 10 bar) / IP 69   |
| Properties            | Excellent shield contact through the contact sleeve with the braided shield terminating in the screwed cable gland |
| Entry thread (G)      | M63x1.5  |
| Clamping range min.   | 46.0 mm  |
| Clamping range max.   | 50.0 mm  |
| Wrench size           | 70 mm  |
| Dimension (H)         | 39 mm  |
| Thread length (L)     | 14 mm  |
| Dispatch              | 5  |

## Available on request:

- Entry thread Pg and NPT