


## Cable glands Progress® nickel-plated brass elbow 90°



### Long entry thread Pg

- Two-piece sealing insert
- not overall length insulated

|                                    |                                      |
|------------------------------------|--------------------------------------|
| <b>Article no:</b>                 | <b>5210.07</b>                       |
| EAN:                               | 7611614128962                        |
| Material                           | Nickel-plated brass                  |
| Seal                               | TPE                                  |
| Operation temperature              | -40°C / +100°C                       |
| Protection class                   | IP 68                                |
| Entry thread                       | IP 68, if the entry thread is sealed |
| Entry thread (G)                   | Pg 7                                 |
| Clamping range with insert min.    | - mm                                 |
| Clamping range with insert max.    | - mm                                 |
| Clamping range without insert min. | 5.0 mm                               |
| Clamping range without insert max. | 6.5 mm                               |
| Wrench size                        | 15 mm                                |
| Dimension (H)                      | 30 mm                                |
| Thread length (L)                  | 11 mm                                |
| Dimension A                        | 11 mm                                |
| Dimension B                        | 32 mm                                |
| Note                               | 1                                    |
| Dispatch                           | 50                                   |

1 = One-piece sealing insert

Available with sealing inserts conformity with EN 45545 / NFPA 130. When placing an inquiry, prefix the article number by the capital F.