


CUGNOT Xtrem

ø100 and ø133 tube light for extreme industrial atmospheres



CUGNOT Xtrem

ø100 and ø133 tube light for extreme industrial atmospheres



Designed to withstand extreme environments, the CUGNOT offers reliability and robustness, built to last, anywhere. Ultra-hermetic to all forms of dust and humidity, it also withstands shocks and vibrations thanks to a one-piece casing that has proved its worth in the harshest of industrial environments. Fully dismantlable and repairable on site, it features LED components among the most robust on the market, capable of supporting high variations in temperature and electrical risk environments.






CUGNOT Xtrem

ø100 and ø133 tube light for extreme industrial atmospheres



Sammode



Disconnectable quick-lock plug version

CRI80, 4000K



Ø (mm)	Flux (lm)	L (mm)	Designation	Code	Watt
100	1850	697	CUG100 12H840 POME PS3 SA BRS	31030020	16
	2775	1007	CUG100 13H840 POME PS3 SA BRS	31030040	24
	3700	1307	CUG100 14H840 POME PS3 SA BRS	31030060	32
	4625	1607	CUG100 15H840 POME PS3 SA BRS	31030080	39
	5550	1850	CUG100 16H840 POME PS3 SA BRS	31030100	46
133	5550	987	CUG133 23H840 POME PS3 SA BRS	32030020	44
	7400	1287	CUG133 24H840 POME PS3 SA BRS	32030040	58
	9250	1587	CUG133 25H840 POME PS3 SA BRS	32030060	72
	11100	1850	CUG133 26H840 POME PS3 SA BRS	32030080	86

One-piece housing, impervious to vibrations, 100% removable and upgradable (Screw system).

Options

Cable entry



Cable gland

Polyamide capacity Ø5-12mm	113
Polyamide capacity Ø7-14mm	116
Nickel-coated brass capacity Ø5-14 mm	113LN
Stainless steel 316L capacity Ø7-13mm	113INOX

Disconnectable plugs

IP68/69K quick-lock plug with threaded ring (capacity: Ø8 to 10 mm)	PS3
---	-----

Fixing straps



Reinforced fixing straps	BRS
Reinforced fixing straps with HSHC screw	BRV

Materials

Polycarbonate housing	PO
Coextruded polycarbonate/PMMA housing with high chemical resistance	POME
End caps & fixing straps 304L stainless steel	-
End caps & fixing straps 316L stainless steel	MR

Color temperature

3000K	830
4000K	840
5000K	850

Lighting management

Electronic gear unit for DALI dimming	RD
---------------------------------------	----

Accessories

To be ordered separately



1m HO7-RNF pre-wired cable 3G1,5 ²	
Stripped free end	CAB0080
Wieland® plug IP68/IP69K (capacity : Ø10-14mm)	CAB0095
Wieland® plug and Y splitter for loop-in/out	CAB0145
Other lengths: consult us	



Folded 304L stainless steel protective cover	
Length 800mm	PU6362
Length 1100mm	CP00595
Length 1400mm	PU6286
Length 1700mm	PU6363
Length 1950mm	CP00597
Also available in 316L : consult us	



304L stainless steel column mounting fixing strap	
Adapter ø1"1/4 (=42mm)	PU4321
Adapter ø1"1/2 (=49mm)	PU4083
Adapter ø2" (=60mm)	PU4082
To order by 2	
Also available in 316L : consult us	



CUGNOT Xtrem

ø100 and ø133 tube light for extreme industrial atmospheres




Sammode


Specification



Photometry



Diameter 100



Diameter 133

Technical characteristics

Light source	High-efficiency removable LED module (CRI>80, 3 SDCM) 70 000 h L80/B10 at max. operating temperature
Optics	Special satin-finish housing for LED Light mixing chamber
Lighting comfort	UGR ≤ 25
Heat management	Aluminium heat sink
Control gear	High reliability constant current output driver, mechanically and thermally reinforced. Resistance to overload: 320 V AC, 48 h Supports voltage spikes < 4 kV Compatible with neutral TN, TT and IT arrangements with no limitations Electronic compatible with central source
Supply voltage	198-264V 0/50/60Hz
Electrical class	Class I
Operating temperature	-20°C to +50°C

Easy installation and maintenance

Connection	With disconnectable plug Ø 8 to 10 mm cable (3 × 1,5 mm ²)
Mounting	Attachment with 2 bolt-fitted stainless steel straps with variable center distance and 360° orientation
LED engine maintenance	Easily removable LED modules and driver Opening by releasing the 2 closing screws, removing the end cap and extracting the gear tray

Materials

Housing	Special polycarbonate housing protected from UV, solvents, hydrocarbons and cleaning agents by a coextrusion of PMMA
End caps and fixing straps	304L stainless steel
Gaskets	Peroxide-cured EPDM
Method of construction	Housing in one piece with high mechanical and chemical resistance Long-lasting imperviousness by axial screw fitting

Standards

Waterproofness	IP66, IP68, IP69K
Resistance to IK shocks	IK10
Fire resistance	650°C
Vibration resistance	Meets the severe application requirements of standard EN 60598-1 (tested according to IEC 60068-2-6)